

Промышленные коммутаторы и медиаконвертеры с PoE

Managed PoE Switches

Operating Temp.: -40 to +75°C; DIN Rail or Wall mounting



NIS-3500-3426PGE

16 10/100/1000Base-T PoE 30W + 2 SFP/1G + 2 TP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- 2 Digital Input (DI), 2 Digital Output (DO)
- Power Input : 48-56VDC; Total PoE Budget: 320W
- Housing: IP30 Protection; Dimensions: 152x107x84mm

✓ 16 ports PoE ✓ Digital Input / Output ✓ Reboot PDs



NIS-3500-3416PGE

16 10/100/1000Base-T (8x PoE 30W) + 4 SFP/1G

NIS-3500-3416PGX

16 10/100/1000Base-T (8x PoE 30W) + 4 1G/10G SFP

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- Power Input : 48-57VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 145x118x93 mm

✓ Digital Input ✓ 10 Gbps ports for uplinks ✓ Reboot PDs



NIS-3500-2408PGX

8 10/100/1000Base-T PoE 30W + 4 1G/10G SFP

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- Power Input : 48-57VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 145x118x72 mm

✓ Digital Input ✓ 10 Gbps ports for uplinks ✓ Reboot PDs



NIS-3500-3226PGE

8 10/100/1000T PoE (2x60W + 6x30W) + 2 SFP/1G + 2 TP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- Power Input : 46-58VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 154x126x72 mm

✓ High-Power PoE 60W ✓ Reboot PDs



NIS-3500-3408PGE

8 10/100/1000Base-T PoE 30W + 4 SFP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- Power Input : 46-58VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 154x126x72 mm



NIS-3500-3224PGE

4 10/100/1000Base-T PoE 30W + 2 SFP/1G + 2 TP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, SSH, Radius
- Power Input : 46-58VDC; Total PoE Budget: 120W
- Housing: IP30 Protection; Dimensions: 154x126x72 mm



NIS-3500-3204PGE

4 10/100/1000Base-T PoE 30W + 2 SFP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog, G.8032 ERPSv2
- Power Input : 48-56VDC; Total PoE Budget: 144W
- Housing: IP30 Protection; Dimensions: 135x88x50 mm

✓ G.8032 ERPSv2 ✓ Reboot PDs



NIS-3500-3208PC

8 10/100Base-TX PoE 30W + 2 SFP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- IGMP, STP, RSTP, MSTP, DHCP 82, LACP, QoS, VLAN
- Telnet, CLI, Web, SNMP, RMON, Syslog,
- Power Input : 46-58VDC; Total PoE Budget: 200W
- Housing: IP30 Protection; Dimensions: 150x125x48 mm

Unmanaged PoE Switches **Operating Temp.: -40 to +75°C; DIN Rail or Wall mounting**



NIS-3200-208PSG

8 10/100/1000Base-T PoE 30W + 2 TP/SFP Combo

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3at/802.3af
- 16K MAC, 2Mbit buffer, Switch fabric 21 Gbps
- POE Pin Assignment: 1/2(+), 3/6(-). Mode A EndSpan PoE
- Power Input : 48-56VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 156x120x48 mm



NIS-3200-464PSG

4 10/100/1000T PoE (2x95W + 2x30W) + 2 SFP/1G + 2 TP/1G

- IEEE 802.3/802.3u/802.3ab/802.3x/802.3bt/802.3af
- 4K MAC, Jumbo Frame 9Kb, PoE ports surge protection 12KV
- POE Pin Assignment: 1/2(+), 3/6(-); 4/5(+), 7/8(-).
- Power Input : 54-56VDC; Total PoE Budget: 240W
- Housing: IP30 Protection; Dimensions: 170x132x40 mm

✓ Ultra PoE 95W



NIS-3200-204PSG-64

4 10/100/1000Base-T PoE 60W + 2 SFP/1G

NIS-3200-204PSG-62

2 TP/1G PoE 60W + 2 TP/1G PoE 30W + 2 SFP/1G

NIS-3200-204PSG-61

1 TP/1G PoE 60W + 3 TP/1G PoE 30W + 2 SFP/1G

- Total PoE Budget: 240W; Dimensions: 142x105x43 mm

✓ High-Power PoE 60W



NIS-3200-205PSG

4 10/100/1000T PoE 30W + 1 SFP/1G + 1 TP/SFP Combo

NIS-3200-205PSGB

24-56VDC Booster

4 10/100/1000T PoE 30W + 1 SFP/1G + 1 TP/SFP Combo

- Power Input : 48-56VDC; Total PoE Budget: 120W
- Housing: IP30 Protection; Dimensions: 142x105x43 mm

✓ Built-in Voltage Booster 24-56VDC

PoE Media Converter **Operating Temp.: -40 to +75°C; DIN Rail or Wall mounting**



NIC-3200-161PCG

1 SFP/1G + 1 TP/1G High-Power PoE 60W

NIC-3200-101PCG

1 SFP/1G + 1 TP/1G PoE 30W

- Total PoE Budget: 60W or 30W; Dimensions: 104x82x32 mm

✓ High-Power PoE 60W



NIC-3200-102PCG

1 SFP/1G + 1 TP/1G + 2 TP/1G PoE 30W

NIC-3200-102PCGB

1 SFP/1G + 1 TP/1G + 2 TP/1G PoE 30W, 24-56VDC Booster

NIC-3200-163PCG

1 SFP/1G + 2 TP/1G + 1 TP/1G High-Power PoE 60W

NIC-3200-163PCGB

1 SFP/1G + 2 TP/1G + 1 TP/1G PoE 60W, 24-56VDC Booster

- Total PoE Budget: 60W; Dimensions: 142x105x37 mm

✓ High-Power PoE 60W ✓ Built-in Voltage Booster 24-56VDC

Промышленные PoE-удлинители, PoE-инжекторы

PoE Extenders



NRP-192PRi **Ultra PoE Extender**
 3 Ethernet TP/1G + Ultra PoE 95W/60W/30W, Booster, 1 PD/2 PSE

- It is possible to cascade 4 devices into a chain up to 500 m
- Compensation of voltage drop in the chain (built-in Booster)
- 1 port PD IN up to 95W + 2 ports PSE OUT 75W/60W/30W/15W
- Housing: IP65/IK10, Wall mounting, Waterproof RJ45 connectors
- Operating Temperature: -40 to +75°C; Dimensions: 190x85x65mm

- ✓ Gigabit Ethernet
- ✓ Built-in Voltage Booster
- ✓ Waterproof RJ45 connectors
- ✓ 95W_60W_30W_15W PoE



NRP-172PRi **High-Power PoE Extender**
 3 Ethernet TP/1G + PoE 72W/60W/30W, Booster, 1 PD/2 PSE

- It is possible to cascade 4 devices into a chain up to 500 m
- Compensation of voltage drop in the chain (built-in Booster)
- 1 port PD IN up to 72W + 2 ports PSE OUT 60W/30W (54VDC or 24VDC)
- Housing: IP67/IK10, Wall mounting, Waterproof RJ45 connectors
- Operating Temperature: -40 to +65°C; Dimensions: 167x73x40mm

- ✓ Gigabit Ethernet
- ✓ Built-in Voltage Booster
- ✓ Waterproof RJ45 connectors
- ✓ > 60W_30W 54 or 24VDC PoE



NRP-161PRi / NRP-162PRi **High-Power PoE Extender**
 2-3 Ethernet 10/100Base-TX + PoE 72W/60W/30W, 1 PD/ 1-2 PSE

- NRP-161PRi: 1 PD IN up to 72W + 1 PSE OUT 70W/60W/30W
- NRP-162PRi: 1 PD IN up to 72W + 2 PSE OUT 70W/60W/30W
- Housing IP67/IK10, Wall mounting, Waterproof RJ45 connectors
- Dimensions NRP-161PRi: 157x56x40mm, Weight: 0.3kg
- Dimensions NRP-162PRi: 167x73x40mm, Weight: 0.36kg
- Operating Temperature: -40 to +65°C

- ✓ Waterproof RJ45 connectors
- ✓ Weatherproof Housing



NRP-111PR / NRP-111PRi **PoE Extender**
 2 Ethernet 10/100/1000T + PoE 30W, 1 PD/ 1 PSE

NRP-101PR / NRP-101PRi **PoE Extender**
 2 Ethernet 10/100Base-TX + PoE 30W, 1 PD/ 1 PSE

- 1 port PD IN up to 30W + 1 port PSE OUT 30W/15W
- Operating Temp.: NRP-1x1PR 0 to +50°C; NRP-1x1PRi -40 to +50°C
- Dimensions: NRP-1x1PR 95x72x27mm; NRP-1x1PRi 140x120x70mm

PoE Injectors



NIP-191PG **Ultra PoE Injector 90-95W**
 1 10/100/1000T Ultra PoE Injector 95W, External 48-56VDC

- 95 watts of maximum power with an input voltage of 56VDC
- POE Pin Assignment: 1/2(+), 3/6(-) & 4/5(+), 7/8(-)
- Reverse polarity / Over voltage / Overload protections
- Housing: IP30 Protection, DIN Rail or Wall mounting
- Operating Temp.: -40 to +75°C; Dimensions: 104x82x32 mm

- ✓ Gigabit Ethernet
- ✓ 95W_60W_30W PoE



NIP-171PG / NIP-171PGB **High-Power PoE Injector 72W**
 1 10/100/1000Base-T, External PS 48-56VDC / 24-56VDC Booster

NIP-111PG / NIP-111PGB **PoE Injector 30W**
 1 10/100/1000Base-T, External PS 48-56VDC / 24-56VDC Booster

- POE Pin Assignment: 1/2(+), 3/6(-) & 4/5(+), 7/8(-)
- Housing: IP30 Protection, DIN Rail or Wall mounting
- Operating Temp.: -40 to +75°C; Dimensions: 104x82x32 mm

- ✓ Gigabit Ethernet
- ✓ 72W_30W PoE



NIP-404PG **4 ports PoE Injector 30W**
 4 10/100/1000Base-T, External PS 48-56VDC

- 4x 30 watts of maximum power with an input voltage of 56VDC
- POE Pin Assignment: 1/2(+), 3/6(-)
- Operating Temp.: 0 to +50°C; Dimensions: 94x62x20 mm

- ✓ Gigabit Ethernet
- ✓ 4 ports 30W PoE